

**DYNAMAX M2T SUPER HP****Safety data sheet**

(Regulation 1907/2006/EC, amended by 2015/830/EU)

**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY / UNDERTAKING****1.1. Product identifier**

<b>Material Name:</b>	<b>DYNAMAX M2T SUPER HP</b>		
<b>CAS:</b>		<b>EINECS:</b>	
		<b>ELINCS:</b>	

**1.2. Identified uses**

<b>Uses:</b>	Motor oil
--------------	-----------

**1.3. Details of the supplier of the safety data sheet**

<b>Manufacturer/Supplier:</b>	EURO-VAT spol. s r.o.
<b>IČO:</b>	18049397
<b>Address:</b>	Alekšince 231 951 22 Alekšince (Slovakia)
<b>Phone/fax number:</b>	+421 37 7822 326-7
<b>E-mail:</b>	<a href="mailto:eurovat@eurovat.sk">eurovat@eurovat.sk</a> <a href="http://www.eurovat.sk">www.eurovat.sk</a>
<b>Emergency phone number:</b>	National Poisons Information Service: City Hospital, Birmingham B187QH, United Kingdom Phone: +44 121 507 4123 E-mai: <a href="mailto:allistervale@npis.org">allistervale@npis.org</a> , <a href="mailto:sallybradberry@npis.org">sallybradberry@npis.org</a> Website: <a href="http://www.npis.org">www.npis.org</a>

**SECTION 2: HAZARDS IDENTIFICATION**

<b>2.1. Classification of the substance or mixture</b>	<b>Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]</b> Skin Irrit. 2            H315 STOT SE 3              H336 Aquatic Chronic 3      H412
<b>2.2 Label elements</b>	<b>Hazard pictograms (CLP/GHS) :</b>  <b>Signal word:</b> WARNING  <b>H-phrases:</b> H315 Causes skin irritation H336 May cause drowsiness or dizziness H412 Harmful to aquatic life with long lasting effects  <b>P-phrases:</b> P261 Avoid breathing vapours P273 Avoid release to the environment P280 Wear protective gloves/eye protection P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower P403+P233 Store in a well-ventilated place. Keep container tightly closed

## DYNAMAX M2T SUPER HP

2.3 Other hazards	<p>P501 Dispose of contents/container to a hazardous waste in accordance with relevant legislation</p> <p>Contains: distillates (petroleum), chemically neutralized light</p> <p><b>Precautionary statements</b></p> <p><b>Prevention :</b> Do not breathe vapour. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling.</p> <p><b>Response :</b> Get medical attention if you feel unwell. <b>IF SWALLOWED:</b> Call a POISON CENTER or physician if you feel unwell.</p> <p><b>Storage :</b> Store in well closed packing at temperatures of up to 40 °C in a dry room that can be ventilated. Protect against heat and direct sunlight. Do not store near food. Prevent its release to the environment.</p> <p><b>Disposal :</b> Not applicable.</p> <p><b>Supplemental label elements:</b> Not applicable.</p> <p><b>Special packaging requirements</b></p> <p><b>Containers to be fitted with child-resistant fastenings:</b> Not applicable. <b>Tactile warning of danger:</b> Not applicable.</p> <p><b>Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII:</b> Not available.</p> <p><b>Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII:</b> Not available.</p> <p><b>Other hazards which do not result in classification:</b> Not available.</p>
-------------------	---

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Product /ingredient name	CAS	EC	Symbols	Conc.	Registr. no REACH	GHS classification	
distillates (petroleum), hydrotreated heavy paraffinic*	64742-54-7	265-157-1	-	min. 75	01-119484627-25-xxxx	-	-
distillates (petroleum), chemically neutralized light	64742-31-0	265-132-5	GHS07,08,09	max. 21	01-2119537182-45-xxxx	Asp. Tox. 1 Skin Irrit. 2 STOT SE 3 Aquatic Chronic 2	H304 H315 H336 H411

\* The base oils used in the mixtures containing less than 3% DMSO extract by IP 346. According to a note in the classified list of L products are not classified as hazardous substances.

### SECTION 4: FIRST AID MEASURES

<b>4.1 Description of first aid measures</b>	<p><b>Eye contact:</b> Rinse immediately with plenty of water. Seek medical attention if irritation develops.</p> <p><b>Inhalation:</b> Assure fresh air breathing. If you feel unwell, seek medical advice.</p> <p><b>Skin contact:</b> Wash the skin with water and soap and apply skin-protective cream.</p> <p><b>Ingestion:</b> Do not induce vomiting. If the injured is conscious give 2 glasses of water. Ensure medical assistance immediately</p>
<b>4.2 Most important symptoms and effects, both acute and delayed</b>	Serious eye damage/eye irritation
<b>4.3 Indication of any immediate medical</b>	Treat symptomatically.

## DYNAMAX M2T SUPER HP

<b>attention and special treatment needed</b>	
---	--

### SECTION 5: FIRE FIGHTING MEASURES

<b>5.1 Suitable extinguishing media</b>	Water fog, carbon dioxide, foam, dry chemical product, sand
<b>5.2. Unsuitable extinguishing media</b>	Do not use a heavy water stream.
<b>5.3. Specific hazards</b>	Hazardous combustion products may include: Carbon monoxide Carbon dioxide (CO <sub>2</sub> ) Nitrogen oxides (NO <sub>x</sub> ) In case of fire: Gases/vapours, toxic.
<b>5.4. Protective equipment for firefighters</b>	In case of fire: Wear self-contained breathing apparatus. Protective clothing. Wear a self-contained breathing apparatus and chemical protective clothing.
<b>Additional advice</b>	Do not inhale explosion and combustion gases. Move undamaged containers from immediate hazard area if it can be done safely. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

<b>6.1. Personal precautions</b>	Ensure adequate ventilation. Avoid contact with skin and eyes. No smoking.
<b>6.2. Environmental precautions</b>	Do not allow to surface and groundwater. With its breakthrough contact person.
<b>6.3. Clean up methods</b>	Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay sand or other suitable material and dispose of properly. Local authorities should be advised if significant spillages cannot be contained.

### SECTION 7: HANDLING AND STORAGE

<b>7.1. Handling</b>	Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used.
<b>7.2 . Storage</b>	Store in a cool dry place. Keep away from heat.

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

<b>8.1. Control parameters</b>	Ventilation respectively. exhausting work areas. The work may not be readily combustible substances and other dangerous source of fire.
<b>8.2 Exposure controls</b>	Observe the usual precautions for health at work and in good ventilation. When using do not eat, drink or smoke.
<b>8.2.1 Occupational exposure controls</b>	<ul style="list-style-type: none"> <li>a) Respiratory protection: the use of Filter type A (EN 141) is recommended if exceeding the Occupational Exposure Limit.</li> <li>b) Eye protection: chemical goggles or safety glasses (EN 166)</li> <li>c) Protection of hands: Wear suitable gloves resistant to chemical penetration (EN 374)</li> <li>d) Skin protection: Wear suitable protective clothing (EN 465, EN 466 or EN 467)</li> </ul> Other: Protective helmet. Do not wear leather soled shoes.
<b>8.2.2. Environmental exposure controls</b>	To prevent leakage of concentrated mixture into surface water drains or soil. Mixture stored in tightly sealed and labeled containers.
<b>8.3. TWA</b>	Occupational Exposure Standard (OES) of 5mg/m <sup>3</sup> , 8-hour time-weighted average reference period for oil mist.

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 Information on basic physical and chemical properties

## DYNAMAX M2T SUPER HP

<b>Fysical state</b>	Oily liquid
<b>Colour</b>	red
<b>Odour</b>	Light odour of petroleum
<b>pH</b>	not available
<b>Flash point (ASTM-D92) [°C]</b>	> 70
<b>Boiling point ( ASTM D1120) [°C]</b>	> 180
<b>Melting point [°C]</b>	- 30
<b>Flammability</b>	IV. class
<b>Temperature of spontaneous combustion [°C]</b>	not available
<b>Lower limit of explosion</b>	not available
<b>Superior limit of explosion</b>	not available
<b>Oxidising properties</b>	not available
<b>Vapour pressure [hPa]</b>	not available
<b>Relative density [g.cm<sup>-3</sup>] at 15°C</b>	approx. 0,880
<b>Water solubility [g.l<sup>-1</sup>]</b>	material insoluble in water
<b>Solubility in solvents [g.l<sup>-1</sup>]</b>	soluble in benzin, toluen
<b>9.2 Other information</b>	
<b>Viscosity at 40°C [mm<sup>2</sup>.s<sup>-1</sup>] typ.</b>	-
<b>Viscozity at 100°C [mm<sup>2</sup>.s<sup>-1</sup>] typ.</b>	>20,5

### SECTION 10: STABILITY AND REACTIVITY

<b>10.1 Reactivity</b>	No specific test data related to reactivity available for this product or its ingredients.
<b>10.2 Chemical stability</b>	Stabile under recommended conditions of use and storage.
<b>10.3 Possibility of hazardous reactions</b>	Under normal conditions of storage and use, hazardous reactions will not occur.
<b>10.4 Conditions to avoid</b>	Extremes of temperature and direct sunlight
<b>10.5 Incompatible materials</b>	Strong oxidising agents
<b>10.6 Hazardous decomposition products</b>	Hazardous decomposition products are not expected to form during normal storage

### SECTION 11: TOXICOLOGICAL INFORMATION

<b>11.1 Information on toxicological effects</b>	<p><b><u>Acute toxicity</u></b></p> <p><b>Acute oral toxicity</b></p> <p><u>Distillates (petroleum), hydrotreated heavy paraffinic:</u> LD50 (rat) &gt; 5 000 mg/kg</p> <p><u>Distillates (petroleum), chemically neutralized light:</u> LD50 (rat) &gt; 5 000 mg/kg</p> <p><b>Acute dermal toxicity</b></p> <p><u>Distillates (petroleum), hydrotreated heavy paraffinic:</u> LD50 (rabbit) &gt; 5 000 mg/kg</p> <p><u>Distillates (petroleum), chemically neutralized light:</u> LD50 (rabbit) &gt; 2 000 mg/kg</p> <p><b>Acute inhalation toxicity</b></p> <p><u>Distillates (petroleum), hydrotreated heavy paraffinic:</u> LC50 (rat) &gt; 5,0 mg/l</p> <p><u>Distillates (petroleum), chemically neutralized light:</u> LC50 (rat) &gt; 5 280 mg/kg 4 h.</p>
--	--

**DYNAMAX M2T SUPER HP**

	<p><b><u>Irritation/Corrosion</u></b> Causes serious eye damage.</p> <p><b><u>Sensitisation</u></b> Conclusion/Summary : Not available.</p> <p><b><u>Mutagenicity</u></b> Conclusion/Summary : Not available.</p> <p><b><u>Carcinogenicity</u></b> Conclusion/Summary : Not available.</p> <p><b><u>Reproductive toxicity</u></b> Conclusion/Summary : Not available.</p> <p><b><u>Teratogenicity</u></b> Conclusion/Summary : Not available.</p> <p><b><u>Aspiration hazard</u></b> Not available.</p> <p><b>Other information :</b> Not available.</p>
--	--

**SECTION 12: ECOLOGICAL INFORMATION**

<b>12.1 Toxicity</b>	Not available.
<b>12.2 Persistence and degradability</b>	Expected to be not readily biodegradable. Major constituents are expected to be inherently biodegradable, but the product contains components that may persist in the environment.
<b>12.3 Bioaccumulative potential</b>	Contains components with the potential to bioaccumulate.
<b>12.4 Mobility</b>	Liquid under most environmental conditions. Floats on water. If it enters soil, it will adsorb to soil particles and will not be mobile.
<b>12.5 Results of PBT and vPvB assessment</b>	<b>PBT :</b> Not available. <b>vPvB :</b> Not available.
<b>12. 6 Other adverse effects</b>	Product is a mixture of non-volatile components, which are not expected to be released to air in any significant quantities. Not expected to have ozone depletion potential, photochemical ozone creation potential or global warming potential.

**SECTION 13: DISPOSAL CONSIDERATIONS**

**DYNAMAX M2T SUPER HP****13.1 Product****Material disposal**

Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water courses.

**13.2. Packing****Container disposal**

Dispose in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.

**Local legislation**

Disposal should be in accordance with applicable regional, national, and local laws and regulations.

EU Waste Disposal Code (EWC):

13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils

13 02 06 synthetic-based non-chlorinated engine, gear and lubricating oils Classification of waste is always the responsibility of the end user.

Classification of waste is always the responsibility of the end user.

**SECTION 14: TRANSPORT INFORMATION**

<b>Transport by land RID/ADR</b>	Not regulated
<b>Transport by sea IMDG</b>	Nor regulated
<b>Transport by air</b>	Not regulated
<b>Additional information</b>	Does not pose a hazard during transport and does not require special treatment (handling) procedure.

**SECTION 15: REGULATORY INFORMATION****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU**

**Annex XIV - List of substances subject to authorisation****Substances of very high concern**

None of the components are listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles:** Not applicable.

**EU Regulation (EC) No 1272/2008 of the European Parliament and of the Council****Other EU regulations**

**Europe inventory :** All components are listed or exempted

**Black List Chemicals :** Not listed

**Priority List Chemicals :** Not listed

**Integrated pollution prevention and control list (IPPC) - Air:** Not listed

**Integrated pollution prevention and control list (IPPC) - Water:** Not listed

**International regulations**

**Chemical Weapons Convention List Schedule I Chemicals:** Not listed

**Chemical Weapons Convention List Schedule II Chemicals:** Not listed

**Chemical Weapons Convention List Schedule III Chemicals:** Not listed

**15.2 Chemical Safety Assessment**

This product contains substances for which Chemical Safety Assessments are still required.

**SECTION 16: OTHER INFORMATION**

## DYNAMAX M2T SUPER HP

### Reason for Revision:

09.02.2020 - Classification of the mixture of the European Parliament and Council Regulation (EC) No. 2015/830 (change of composition and classification in Section 2 and 3)

### 16.1 Text of H-phrases (point 3):

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

### 16.3 Other information:

The information above is based on a current available data concerning the product, but also on the experience and knowledge in this field of the producer. They are neither a quality description of the product nor a guarantee of particular features. They are to be treated as aid to safety in transport, storage and usage of the product. This does not free the user from the responsibility of improper usage of the information above and also of improper compliance with the law norms in the field.